PAIDC

QUERY CONTROL FORM					RTIS USE ONLY	
Application No.	09	674,822	Prepared by	JI.H.	Tracking Number	05815647
Examiner-GAU		enberger-		2-2-4	Week Date	12/15/03
			No. of queries	l	IFW	

JACKET					
a. Serial No.	f. Foreign Priority	k. Print Claim(s)	p. PTO-1449		
b. Applicant(s)	g. Disclaimer	I. Print Fig.	q. PTOL-85b		
c. Continuing Data	h. Microfiche Appendix	m. Searched Column	r. Abstract		
d. PCT	i. Title	n. PTO-270/328	s. Sheets/Figs		
e. Domestic Priority	j. Claims Allowed	o. PTO-892	t. Other		

SPECIFICATION	MESSAGE
a. Page Missing	No abstract in file. Please supply.
b. Text Continuity	
c. Holes through Data	
d. Other Missing Text	-
e. Illegible Text	
f. Duplicate Text	
g. Brief Description	·
h. Sequence Listing	
i. Appendix	
j. Amendments	
k. Other	
CLAIMS	
a. Claim(s) Missing	
b. Improper Dependency	thankyou
c. Duplicate Numbers	
d. Incorrect Numbering	initials \mathcal{N},\mathcal{H} .
e. Index Disagrees	RESPONSE
f. Punctuation	
g. Amendments	i ch
h. Bracketing	12 fd.
i. Missing Text	
j. Duplicate Text	
k. Other	
	initials

ABSTRACT OF THE DISCLOSURE

A method and apparatus for surface measurement using the shadow moire effect with the Talbot effect. The apparatus includes a specimen mount to receive a specimen having a surface to be measured, and a reference grating mounted adjacent to the specimen mount so as to be substantially parallel to a mean surface plane of the specimen. The reference grating is mounted in such a manner that the distance between the reference grating and the mean surface plane of the specimen can be adjusted to a Talbot distance δT . The apparatus also includes a light source to illuminate the specimen through the grating and a detector positioned to detect the moire fringes produced by the grating due to variation of the surface of the specimen.